

TURBOSOUND LEGACY PRODUCTS	Gain dB	Polarity	Delay ms	HPF	LPF	Limiter dB	EQ
Flashlight and Floodlight							
Qlight							
TFM							
TMS							
TCS							

Name	Gain	Polarity	Delay	High-pass Slope	Freq	Low-pass Slope	Freq	PEQ1 BW	Gain	Freq	PEQ2 BW	Gain	Freq	PEQ3 BW	Gain	LIMITERS dBu
------	------	----------	-------	--------------------	------	-------------------	------	------------	------	------	------------	------	------	------------	------	-----------------

HIGHLIGHT																						
TQ-300 Series																						
Name	Gain	Polarity	Delay	High-pass Slope	Freq	Low-pass Slope	Freq	PEQ1 Q	Gain	Freq	PEQ2 Q	Gain	Freq	PEQ3 Q	Gain	Freq	PEQ4 Q	Gain	Freq	PEQ5 Q	Gain	
TQ-308	0,0	+	0,000	24dB BW		OUT	80,3	3,0	7,4	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-308	0,0	+	0,000	24dB BW		OUT	80,3	3,0	7,4	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-115	0,0	+	0,000	24dB BW	125Hz	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-308	0,0	+	0,000	24dB BW	OUT	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-115	0,0	+	0,000	24dB BW	125Hz	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-308	0,0	+	0,000	24dB BW	OUT	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-425	-3,0	+	0,000	24dB BW	125Hz	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-308	0,0	+	0,000	24dB BW	OUT	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-425	-3,0	+	0,000	24dB BW	125Hz	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-308	0,0	+	0,000	24dB BW	OUT	24dB BW	80,3	3,0	0,0	1,56	3,4	-6,0	7,85kHz	5,0	-2,1	10,3kHz	1,0	-7,0				
TQ-310	0,0	+	0,000	24dB BW		OUT	66,2	1,6	9,5	735	4,0	-2,2	2k88	2,0	-6,0	7k85	5,0	-2,2	12k7	1,2	-8,0	
TQ-310	0,0	+	0,000	24dB BW		OUT	66,2	1,6	9,5	735	4,0	-2,2	2k88	2,0	-6,0	7k85	5,0	-2,2	12k7	1,2	-8,0	
TQ-115	3,0	+	0,000	24dB BW	125 Hz	24dB BW	66,2	1,6	0,0	735	4,0	-2,2	2k88	2,0	-6,0	7k85	5,0	-2,2	12k7	1,2	-8,0	
TQ-310	0,0	+	0,000	24dB BW	125 Hz	24dB BW	66,2	1,6	0,0	735	4,0	-2,2	2k88	2,0	-6,0	7k85	5,0	-2,2	12k7	1,2	-8,0	
TQ-115	3,0	+	0,000	24dB BW	OUT	24dB BW	66,2	1,6	0,0	735	4,0	-2,2	2k88	2,0	-6,0	7k85	5,0	-2,2	12k7	1,2	-8,0	
TQ-310	0,0	+	0,000	24dB BW	OUT	24dB BW	66,2	1,6	0,0	735	4,0	-2,2	2k88	2,0	-6,0	7k85	5,0	-2,2	12k7	1,2	-8,0	
TQ-310 Monitor	0,0	+	0,000	24dB LR		OUT	420	4,0	-5,5	735	3,0	-2,2	2k88	2,0	-5,0	7k85	5,0	-1,6	12k7	1,2	-4,0	
TQ-310 Monitor	0,0	+	0,000	24dB LR		OUT	420	4,0	-5,5	735	3,0	-2,2	2k88	2,0	-5,0	7k85	5,0	-1,6	12k7	1,2	-4,0	
TQ-315 Passive	0,0	+	0,000	24dB BW		OUT	71,5	1,5	10,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0	6k6	6,0	-2,0	
TQ-315 Passive	0,0	+	0,000	24dB BW		OUT	71,5	1,5	10,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0	6k6	6,0	-2,0	
TQ-425	2,0	+	0,000	24dB BW	125 Hz	24dB BW	71,5	1,5	0,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0	6k6	6,0	-2,0	
TQ-315 Passive	0,0	+	0,000	24dB BW	125 Hz	24dB BW	71,5	1,5	0,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0	6k6	6,0	-2,0	
TQ-315 Passive	0,0	+	0,000	24dB BW	OUT	24dB BW	71,5	1,5	0,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0	6k6	6,0	-2,0	
TQ-315 Passive Monitor	0,0	+	0,000	24dB BW		OUT	437	3,0	-2,0	721	5,0	-4,0	3k5	2,1	-10,5	6k35	4,0	-2,4	1k62	2,5	-1,5	
TQ-315 Passive Monitor	0,0	+	0,000	24dB BW		OUT	437	3,0	-2,0	721	5,0	-4,0	3k5	2,1	-10,5	6k35	4,0	-2,4	1k62	2,5	-1,5	
TQ-315 Biamp LF	0,0	+	0,344	24dB BW	1k44	12dB BW	71,5	1,5	10,0	260	5,0	-2,2	735	6,0	-3,0							
TQ-315 Biamp HF	-1,5	-	0,000	12dB BW	OUT		4k76	1,2	-6,2	8k98	8,0	-5,0	11k8	4,0	1,2	2k	3,6	-2,5				
TQ-315 Biamp LF	0,0	+	0,344	24dB BW	1k44	12dB BW	71,5	1,5	10,0	260	5,0	-2,2	735	6,0	-3,0							
TQ-315 Biamp HF	-1,5	-	0,000	12dB BW	OUT		4k76	1,2	-6,2	8k98	8,0	-5,0	11k8	4,0	1,2	2k	3,6	-2,5				
TQ-425	2,0	+	0,000	24dB BW	125	24dB BW	71,5	1,5	0,0	260	5,0	-2,2	735	6,0	-3,0							
TQ-315 Biamp LF	0,0	+	0,344	24dB BW	1k44	12dB BW	71,5	1,5	0,0	260	5,0	-2,2	735	6,0	-3,0							
TQ-315 Biamp HF	-1,5	-	0,000	12dB BW	OUT		4k76	1,2	-6,2	8k98	8,0	-5,0	11k8	4,0	1,2	2k00	3,6	-2,5				
TQ-315 Biamp Monitor LF	0,0	+	0,344	24dB BW	1k33	24dB BW	437	3,0	-2,0	260	5,0	-1,5	721	6,0	-2,5	1k12	6	3,5				
TQ-315 Biamp Monitor HF	0,0	+	0,000	18dB BW	OUT		3k43	2,1	-10,0	6k35	4,0	-1,9	8k98	8,0	-5,0	11k8	5,0	2,1				
TQ-315 Biamp Monitor LF	0,0	+	0,344	24dB BW	1k33	24dB BW	437	3,0	-2,0	260	5,0	-1,5	721	6,0	-2,5	1k12	6	3,5				
TQ-315 Biamp Monitor HF	0,0	+	0,000	18dB BW	OUT		3k43	2,1	-10,0	6k35	4,0	-1,9	8k98	8,0	-5,0	11k8	5,0	2,1				
THL-828	0,0	+	0,000	24dB BW	125 Hz	24dB BW																
TQ-315 Passive	0,0	+	3,499	24dB BW	OUT		71,5	1,5	0,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0	6k6	6,0	-2,0	
THL-828	0,0	+	0,000	24dB BW	125 Hz	24dB BW																
TQ-315 Passive	0,0	+	3,499	24dB BW	OUT		71,5	1,5	0,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0	6k6	6,0	-2,0	
THL-828	0,0	+	0,000	24dB BW	125	24dB BW																
TQ-315 Biamp LF	0,0	+	0,000	24dB BW	1k44	12dB BW	71,5	1,5	0,0	260	5,0	-2,2	735	6,0	-3,0							

TURBOSOUND LEGACY PRODUCTS	Gain dB	Polarity	Delay ms	HPF	LPF	Limiter dB	EQ											
TQ-315 Blamp HF	-1,5	-	3,165	12dB BW	OUT		4k76	1,2	-6,2	8k98	8,0	-5,0	11k8	4,0	1,2	2k00	3,6	-2,5
THL-818	3,0	+	0,000	24dB BW	125 Hz	24dB BW												
TQ-315 Passive	0,0	+	3,499	24dB BW	OUT		71,5	1,5	0,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0
THL-818	3,0	+	0,000	24dB BW	125 Hz	24dB BW												
TQ-315 Passive	0,0	+	3,499	24dB BW	OUT		71,5	1,5	0,0	721	5,0	-3,0	4k32	1,6	-8,0	8k98	8,0	-5,0
Flashlight Mk 2																		
Aspect V1 Hornflare Assembly																		
TXD Series																		
TCS Compact Series																		
TQ-400 Series																		

Note, gain structure will change depending on configuration

** 18dB Butterworth slope

* 24dB Butterworth slope